

Domus IF



Equipped with:

- 2 silenced two stage motor.
- Suction system with by-pass cooling.
- S. S. tank.
- Professional closing hooks.
- Static electric shock inhibitor.
- Drain hose system.
- Shock proof trolley.
- Liquid float valve.
- Cloth filter.
- 10 m power cable.
- Easy standing head (during filter cleaning).
- Traceless wheels.
- Accessories Ø 40.

STANDARD EQUIPMENT

- 5.209.0021 Hose 2,5 r 
- 6.205.0126 
- 3.754.0048 
- 3.754.0049 
- 3.754.0083 400 mm 
- 3.754.0084 
- 3.754.0085 
- 5.509.0039 Cloth filter 

Optional:

- 5.212.0022 Paper collector filter set (10 pcs)
- 5.509.1405 Cloth filter for fine dust
 - 5.212.0093 Nylon filter
 - 5.212.0021 Washable filter
 - 5.212.0034 HEPA filter

	Domus IF
code	8.216.0502
voltage	220-240V ~ 50-60Hz
n°motors - power (max)	2 - 2000 (2400) W silenced two stage motor
column depression	22 kPa/2240 mmH ₂ O
air suction	108 l/s
total volume/dust/liquid	78 l./35 l./48 l.
dimension/weight	62x51x85 cm / 28 kg