



- Electrode holder clamp for MMA welding.
- Maximum current 300 A.
- Cable diameter max 25 mm<sup>2</sup>.
- Sale quantity 10 pieces.

## TECHNICAL DATA

---

CODE	<b>804170</b>	T04050	<b>25 max mm<sup>2</sup></b>
MAX CURRENT	<b>300 A</b>	WEIGHT	<b>0,320 kg</b>

## DESCRIPTION

---

Professional electrode holder welding clamp for welding currents up to 300A. It can be installed on cables with section up to 25 mm<sup>2</sup>. It is made using high conductivity materials to guarantee high performance; complete insulation of the structure ensures maximum protection and safety for the operator.

## DOWNLOAD

---



CATALOG IMAGE

## DALLAS 400 ELECTRODE HOLDER 400A



- Electrode holder clamp for MMA welding.
- Maximum current 400A.
- Max cable diameter 50mm<sup>2</sup>.
- In cardboard box.

## TECHNICAL DATA

---

CODE	<b>802770</b>	T04050	<b>50 max mm<sup>2</sup></b>
MAX CURRENT	<b>400 A</b>	WEIGHT	<b>0,520 kg</b>

## DESCRIPTION

---

Professional electrode holder welding clamp for welding currents up to 400A. It can be installed on cables with section up to 50 mm<sup>2</sup>. It is made using high conductivity materials to guarantee high performance; complete insulation of the structure ensures maximum protection and safety for the operator.

## DOWNLOAD

---



CATALOG IMAGE

## DALLAS 600 ELECTRODE HOLDER 600A



- Electrode holder clamp for MMA welding.
- Maximum current 600A.
- Max cable diameter 70mm<sup>2</sup>.
- In cardboard box.

## TECHNICAL DATA

---

CODE	<b>802785</b>	T04050	<b>70 max mm<sup>2</sup></b>
MAX CURRENT	<b>600 A</b>	WEIGHT	<b>0,500 kg</b>

## DESCRIPTION

---

Professional electrode holder welding clamp for welding currents up to 600A. It can be installed on cables with section up to 70 mm<sup>2</sup>. It is made using high conductivity materials to guarantee high performance; complete insulation of the structure ensures maximum protection and safety for the operator.

## DOWNLOAD

---



CATALOG IMAGE

